



TAKE CHARGES OF YOUR SAETY



Large terminal capacity
(upto 35 sq. mm)



Safety sliding shutters



Line load reversible



Breathing channels

**Domestic Switchgear
2020**

***WARRANTY:** Warranty for a period of five years when fitted in STANDARD distribution boards. When fitted in any other distribution board, warranty period is one year.

Miniature Circuit Breaker (MCB)

Range

6 A - 40 A (B Type) / 0.5 A - 63 A (C Type)

Execution

SP, SPN, DP, TP, TPN, FP

Specification

IS / IEC : 60898-1 / 2002

Features

- Safety sliding shutters
- Two position DIN rail clamp
- Breathing channels
- Large terminal capacity



MCB Changeover Switch

Range

25 A, 40 A, & 63 A

Execution

Double Pole (2P), Four Pole (4P)

Specification

IS / IEC 60947 - 3

Features

- Compact construction & Double break contacts
- Silver Cadmium Oxide contact tips
- Shrouded terminals
- Front operation with three stable positions I-O-II
- Centre position OFF
- Easy snap on DIN Rail mounting
- Can be mounted with other products viz. MCB, RCCB, Isolator in Distribution Board



ACCL & Auto C/o

Range

30 A / 1 A to 15 A

Execution

Single Pole & Neutral

Poles

3 m

Features & Benefits

- High Precision: electronic Device
- Advance Neutral Device
- Inbuilt Current Limiting Function
- Auto Restoration to Primary Supply
- Compact Size; energy efficient Device
- LED Indication



Residual Current Circuit Breaker (RCCB)

Range

16 A, 25 A, 40 A, 63 A, 80 A & 100 A

Execution

Double Pole (2 P), Four Pole (4 P)

Sensitivity

30 mA, 100 mA, 300 mA

Specification

IS 12640-1: IEC/ EN 61008-1

Features

- Simple and Robust operating mechanism.
- Dual termination for Bus Bar as well as cable connection
- Test Button for regular inspection. & Advance Neutral.
- Protection against leakage current & Fire Hazards.
- Safety sliding shutters for installers.



Isolator

Range

40 A, 63 A, 100 A, 125 A

Execution

SP, DP, TP, FP

Specification

IS / IEC 60947 - 3

Features

- Low Watt Loss
- Longer electrical life
- Wide range availability
- Low power consumption, thus cost effective & energy saving



Residual Current Circuit Breaker with Overload & Short Circuit Protection (RCBO)

Range

6 A, 10 A, 16 A, 20 A, 25 A, 32 A & 40 A

Sensitivity

30 mA, 100 mA, 300 mA

Execution

SPN & TPN

Specification

IS 12640 (Part 2) & IEC 61009

Features

- Pulsating DC protection - Type 'A'
- Discrimination using time delay - Type S RCBO
- Controlled response VD RCBO (Electronic)
- Protection in case of loss of supply neutral
- Enhanced immunity to nuisance tripping
- Short circuit breaking capacity 10 kA
- Large terminal capacity : RCBOs have 35 mm 2 for cool running while in operation.



MCB Distribution Boards

Range

SPN - 4, 6, 8, 12, 16 Ways, TPN - 4, 6, 8 & 12 Ways

Specification

IS 13032 & IEC : 61439 -3

Degree of Protection

IP 42

Suitable for Incoming

2 pole or 4 pole

Features

- Aesthetically Pleasing Design
- Elegant Color combination
- Door earthing for extra protection
- Transparent cement guard to protect the DB from construction spill over.



MCB Distribution Boards

Range

SPN - 4 way, 6 way, 8 way, 12 way, 16 way & 2+4 way, 2+6 way, 2+8 way, 2+10 way, 2+12 way, 2+14 ways TPN - 4 way, 6 way, 8 way & 12 ways

Specification

IS 13032 & IEC : 61439 -3

Degree of Protection

IP 42 & 43

Suitable for Incoming

2 pole or 4 pole

Configurations

Horizontal, Vertical, Consumer Unit, Power line, 7 Segment, MCB Enclosure

Features

- Aesthetically Pleasing Design
- Elegant Color combination
- Corners of the top cover have been beautifully covered with new unique design of side channels
- Transparent cement guard to protect the DB from construction spill over.
- Seven Tank Phosphating Pre-Treatment Process



Special Purpose DBs



PPI DB - Vertical



PPI DB - Horizontal



Phase Selectors DB



7 Segment DB

MCB Protected Socket

Range

25A C Series

Rated Voltage Un

240V AC

Rated Frequency

50 Hz

Execution

1P

Specification

IS 13032 / IS 8623

Terminal Capacity

6 mm²

Features

- Aesthetic appeal
- Ideal for local sectioning - Selectivity
- High quality contacts ensures reliability
- Built in MCBs protection, short circuit breaking capacity (3kA)
- Suitable for protection of home appliances like ACs, LCD, Geyser, Microwave etc.
- Available with Sheet Metal & Plastic Box in 3 & 4 Module



Mini MCB with Enclosure

POWER SHIELD

Range

32 A C Series

Rated Voltage Un

240 V AC

Rated Frequency

50 Hz

Execution

2 P

Specification

IS/IEC: 60898-1

Features

- Appealing & contemporary aesthetics
- compact & space saving design
- Overload & short circuit protection
- Proven MCB mechanism for longer life
- Easy to operate & replace
- Completely insulated design
- Indication of supply



Consumer Unit & Enclosures DBs



Sheet Steel MCB Enclosure



Plastic MCB Enclosure



Consumer Unit



Cable End Box

Regional & Branch Offices:

NORTH - REGIONAL OFFICE: Corporate Office: QRG Towers, 2D, Sector-126, Expressway, Noida-201304, Tel: 0120-3331000, **Delhi:** Tel: 011-47676700, 23888200, **Chandigarh:** Tel: 0172-4232400-401, **Dehradun:** Tel: 0135-6670202, **Noida / Haryana:** Tel: 0120-3331000, **Ludhiana:** Tel: 0161-4676000 / 24, **Jammu:** Tel: 0191-2478330, 2479330, **Sri Nagar:** Tel: 0194-2490431, **Jaipur:** Tel: 0141-3914645, 3988210 **Jodhpur:** Tel: 0291-9214201640 / 45, **Lucknow:** Tel: 0522-6672100, **Kanpur:** Tel: 0512-6710400, 6710409

EAST - REGIONAL OFFICE: Kolkata: ICC Tower, 5th Floor, 4 India Exchange Place, Kolkata-700001, Tel: 033-40129851 / 52, **Bhubaneshwar:** Tel: 0674-6668101/102/103/104, **Guwahati:** Tel: 0361-2134521, 2458923, 2460355, **Siliguri:** Tel: 0353-2525907, **Ranchi:** 0651-2244861, 2244862, 2244864, 2244868, 2244869, **Jamshedpur:** Tel: 0657-6542492, 09234369436, **Patna:** Tel: 0612-2207221, 2207222, 2207223, 2655518

WEST - REGIONAL OFFICE: Mumbai: Mumbai: 1271, Solitaire Corporate Park, Bldg. No. 12, 7th Floor, Andheri - Ghatkopar Link Road, Chakala, Andheri (East), Mumbai-400093. Ph.:022-67298600-602, **Ahmedabad:** Tel:079-40061111, 40060738-740, **Indore:** Tel:0731-2572340-41, 4009998(Airtel), **Rajkot:** Tel:0281-2481112, 2921212, **Nagpur:** Tel: 0712-2240932, 2242692, 2242699 **Pune:** Tel: 020-64016413 / 14, **Raipur:** Tel: 0771-4243400 / 01, **Surat:** Tel: 0261-6131001, 9099056612, **Jabalpur:** Tel: 0761-4064491

SOUTH - REGIONAL OFFICE: Chennai: Sigapi Achi Building, No. 18 / 3, 6th Floor, Rukmani Lakshminpathy Road, Egmore, Chennai-600008, Tel: 044-42280600, 605, **Bangalore:** Tel: 080-49075000, **Coimbatore:** Tel: 0422-2305767, 2306199, 2305199, **Hyderabad:** Tel: 040-27533372, 27533355, 27533632, 66320407/0408/6401/6402, **Kochi:** Tel: 0484-4099000, **Vishakapatnam:** Tel: 0891-6514339, **Vizag:** Tel: 0891-6514339, **Vijayawada:** Tel: 91+9247058847/57, **Calicut:** 09895855499, **Madurai:** 09994493242, **Trivandrum:** 09633817795, **Hubli:** 0836-4248600, **Trichy:** 09944460160

Representative Offices: • Goa • Solapur • Gwalior • Kathmandu • Bhopal

Terms & Conditions :

- Prices are in Indian ₹.
- The List prices are inclusive of GST.
- This Price List supersedes all our previous Price Lists.
- Prices are subject to change without notice.
- Company reserves the right to issue amendments, which may arise due to any errors in the price list.

Actual products may vary in colour, design, description and colour combination etc. Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication. Specifications & performance data are constantly changing.

Havells India Ltd.

Corp Office: QRG Towers, 2D, Sector-126, Expressway, Noida-201304 (U.P),
Ph. +91-120-3331000, E-mail: standard.ho@havells.com, www.standardelectricals.com
Consumer Care No.: 1800 103 1313, 1800 11 0303 (All Connections)
CIN - L31900DL1983PLC016304.

Copyright Subsists. Imitation of trade dress, graphics and color scheme of this document is a punishable offence.

